

Characteristics

- 100% Polyester veil
- Fiber melting point (409°F / 255°C)
- Low cost
- High uniformity
- Good chemical resistance
- Good tensile strength
- Available in custom slit widths
- Good wet-out

Applications

- Superior handling in pultrusion
- Improves weathering
- Reduces fiber blooming
- Reduces die wear and production shutdowns
- Improves abrasion resistance
- Improved part appearance
- Improves impact resistance

Style	Unit	700-13	700-12	700-10
Shade		White	White	White
Basis Weight (ASTM D3776)	(oz/y ²) (g/m ²)	1.2 40	1.0 34	.56 19
Caliper (ASTM D1777)	(mil) (mm)	9 .23	8 .20	5 .13
Grab Tensile (ASTMD5034)				
Machine Direction	(lb) (kg)	21 9	16 7	6 3
Cross Direction	(lb) (kg)	14 6	14 6	5 2
Standard Roll Width	(in) (cm)	60 152	62 157	62 157

Precision Fabrics Group, Inc. believes the information and recommendations here in to be accurate and reliable. However, any specific application or usage of the company's products must be evaluated in the individual context to ensure that the results desired for each application will be obtained. Precision Fabrics Group, Inc. would be pleased to participate in that evaluation process. However, Precision Fabrics Group, Inc. assumes no obligation or liability and does not warranty or guarantee results from the use of any information contained in this document.